



2 Port 10/100/1000M Unmanaged Industrial PoE Switch

OP-S1E1X-I



Shenzhen Optostar Optoelectronics Co., Ltd

2013. 10 (Version 1)

Overview

This unmanaged Ethernet PoE switch is specialized for harsh industrial environment. It is classified as power resource equipment, which can be used to power IEEE 802.3af/at compliant powered devices, eliminates the need of additional wiring.


With simple operation, excellent quality and competitive price, it provides an economical solution for your industrial Ethernet network, which is also specially designed for the needs of multiplex broadband access with limited optical fibers.

Features

- 1 IEEE 802.3af/at PoE compliance 10/100/1000Base-T(X) port and 1 1000Base-SFP port
- Up to 30W at 48V DC power output on each PoE port
- Super lightning protection, IP40 protection
- Excellent heat elimination without cooling fan
- Redundant dual DC power inputs
- -40°C-85°C operating temperature range
- Packet Buffer Size: 1Mbit
- Din-Rail mounting, Wall mounting design, easy to install and use
- MAC Table Size: 1K
- Meets the standards of the IEEE 802.3af/at standard

Technical Indexes

Standard	<p>IEEE 802.3af/at Comply with IEEE802.3u, 1000Base-FX Safety: UL 60950-1 Shock: IEC 60068-2-27 Free Fall: IEC 60068-2-32 Vibration: IEC 60068-2-6 EMI: FCC Part 15 Subpart B Class A, EN 55022 Class A Industry: IEC61000-6-2 Rail: EN50155, EN50121-4 Traffic: NEMA TS-2</p>
EMS	<p>EN61000-4-2 (ESD), Level 3 EN61000-4-3 (RS), Level 3 EN61000-4-4 (EFT), Level 3 EN61000-4-5 (Surge), Level 3 EN61000-4-6 (CS), Level 3 EN61000-4-8, Level 3</p>
Copper Port	<p>1 RJ45 Port Comply with IEEE802.3, IEEE802.3u, 10/100Base-T(X), IEEE802.3af/at PoE, 10/100/1000/Base-T(X) auto negotiation speed Full/Half duplex mode Auto MDI-MDI-X connection Up to 100M Cat-5 transmission distance</p>
Fiber Port	<p>1 Fiber Port Comply with IEEE802.3u, 1000Base-FX Rate: 1000Mbps Wavelength: 850nm/1310nm/1550nm Up to 550M transmission distance with multi-mode Up to 20Km,40Km,60Km,80Km transmission distance with single-mode SC/LC interfaces optional</p>
Switch Properties	<p>MAC Table Size: 1K Packet Buffer Size: 1Mbit Processing Type: Store and Forward Exchange Properties: 148800pps (1000M)</p>
Power	<p>Input Voltage: 48V DC(44-57VDC), Redundant dual inputs Input Current: <0.5A @48VDC Overload Current Protection: Present Reverse Polarity Protection: Present Redundant Protection: Present Connection: 1 removable 6-pin terminal blocks</p>
Environmental Limits	<p>Operating Temperature: -40°C-85°C Storage Temperature: -40°C-85°C Ambient Relative Humidity: 5%-95% (non-condensing)</p>
Warranty	<p>3 years</p>



Physical Characteristics	Housing: Aluminum Alloy material with IP40 Protection Dimension: 138mm(L) X 112mm(W) X 60mm(H) Weight: 640g Installation: Din-Rail mounting, Wall mounting
--------------------------	---

Order Information

Model	Description
OP-S1E1X-I	1 IEEE 802.3af/at PoE compliance 10/100/1000Base-T(X) port and 1 1000Base-SFP port

Note:1. Multi-mode/ Single-mode Optional
2. 550M,2KM,20KM,40KM,60KM,80KM Optional
3. Wavelength: 850nm/1310nm/1550nm
4. SC/ST/FC Optional
5. Dual Fiber/ Single Fiber Optional

Package include

No	Package List
1	1 IEEE 802.3af/at PoE compliance 10/100/1000Base-T(X) port and 1 1000Base-SFP port
2	Power Adapter
3	User Guide
4	Warranty Card

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.

Contact OPTOSTAR

Shenzhen Optostar Optoelectronics Co., Ltd

Address:A-14,Haide Building,the Intersection of Nanxin Road and Haide Second Road Nanshan District Shenzhen,China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: info@optostar.com.cn

Skype:ouyangroya

Web: www.optostar.com.cn