



# Fusion Splicer

OP-FS17



Shenzhen Optostar Optoelectronics Co., Ltd

2013. 02 (Version 2)

## Overview

OP-FS17 FTTH Fusion Splicer, with high performance price ratio, is the main product of SHENZHEN OPTOSTAR. With smart appearance, reliable quality, OP-FS17 is a special design for the installation, operation and maintenance of optical fiber specially design precision, durable, convenient optical fiber construction instrument. Widely used in the construction, inspection, maintenance of fiber cable.

## Product Features

- Used for FTTH and ordinary fiber project
- Core to core alignment by PAS technology
- 8 sec splicing time and 30 sec heat time
- 300 X or Y view, 200 X and Y view
- 5 inch digital high-quality LCD screen, observe X and Y view at same time
- Three in one fixture, splicing single fiber, cable indoor and pig tail
- Built in large capacity lithium battery of 200 times splicing and heating
- Small size and light weight, 2.1KG including battery

## Technical Parameters

Model	OP-FS17 Handheld FTTH Fusion Splicer
Splicing Type	SM, MM, DS, NZDS
Splicing Loss	0.02dB(SM), 0.01dB(MM), 0.04dB(DS), 0.04dB(NZDS)
Return Loss	>60dB
Splicing Mode	Manual, Half Auto, Auto
Fiber Alignment	Core to Core Alignment by PAS technology
Applicable Fiber	Cable indoor and 0.25mm,0.9mm fiber, SC connector(option)
Splicing Time	≤9s

Heat Time	≤30s
Cleaved Length	8~16mm
Fiber Image/ Magnification	300/200
View Display	5 inch digital high-quality LCD screen
Tension Test	Standard 2N (option)
Heat Shrinkable Sleeve	60mm, 40mm and serials heat Shrinkable Sleeve
Battery Capacity	200 cycles splicing and heating, 3 hours charging time ( splicing and charging at same time)
Battery Life	Cycling charge 300-500 times, easy to replace battery
Electrodes Life	3000, easy to replace electrodes
Power Source	≤20W
Interface	USB Convenient data download and software update
Construction Lighting	Built in high brightness, wide range of lights, easy to operate at night
Power supply	Built in lithium battery 5200mAh 11.1V; external adapter, input: AC100-240V, output: DC13.5V/4.5A
Operating Condition	0-5000m above sea level, Temperature: -10-60℃, Humidity:0~95%RH (No dew)
Weight (including battery)	2.1 KG (including battery)
Dimension (LxWxH)	135mm(L)×158mm(W)×155mm(H)

**Kit Include:**

No	Name	Qty
1	Fusion Splicer ( OP-FS17 )	1 set
2	Fiber Cleaver	1 pc
3	Fiber Stripper	1 pc
4	AC Adatpor	1 pc

5	Li Battery	1 pc
6	Charger	1 pc
7	Spare Electrodes	1 pair
8	Cooling Tray	1 pc
9	User Manual CD	1 pc
10	Carrying Case	1 pc

**Image Illustration**



## Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.

## Contact OPTOSTAR

### **Shenzhen Optostar Optoelectronics Co., Ltd**

Address: A-14, Haide Building, the Intersection of Nanxin Road and Haide Second Road Nanshan District Shenzhen, China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: [info@optostar.com.cn](mailto:info@optostar.com.cn)

Skype: ouyangroya

Web: [www.optostar.com.cn](http://www.optostar.com.cn)