



# Optical Light Source

OP-OLS11



Shenzhen Optostar Optoelectronics Co., Ltd

2013. 05 (Version 2)

### Overview

OP-OLS11 optical light source is a handheld optical light source, newly released in 2007. It can provide 1 to 5 wavelengths output to satisfy specific requirements including the 650nm visible light source and the 1310/1550nm wavelengths for single mode fiber or the 850/1300nm wavelengths for multimode fiber, as well as other wavelengths according to customer's needs. Together with the OP-OLS11 optical power meter, it is a perfect solution for fiber optic network applications.

### Product Features

- Provides 1~5 wavelengths output which can be optional according to customers' needs
- CW, 2Hz modulation output at 650nm, and CW, 270Hz,1KHz,2KHz modulation output at other wavelengths.
- High stability of the output power
- Stable output wavelength
- Backlight LCD display supports night operation
- Low battery power indication

### APPLICATIONS

- Maintenance Telecom
- Maintenance CATV
- Test Lab of Fiber Optic
- Optical fiber sensors

### Technical Parameters

Type	OP-OLS11
Wavelengths(nm)	Provides 1~5 Wavelengths according to needs.
Emitter Type	FP-LD,LED
Typical Output	0@650nm / -7 @1310nm,1550nm, -20dBm for LED
Spectral Width(nm)	≤10

Output Stability	±0.05dB/15mins; ±0.1dB/ 8hours
Modulation Frequencies	CW,2Hz@650nm / CW,270Hz,1KHz,2KHz@1310nm,1550nm
Optical Connector	FC/PC(Other type adapters can be required)
Power Supply	Alkaline Battery(3 AA 1.5V batteries); AC Adaptor(9V)
Battery Operating	45
Operating	-10~+60
Storage Temperature(°C)	-25~+70
Dimension(mm)	190X100X50
Weight(g)	370
OPTOSTAR Recommendation	
OP-OLS11 Handheld Light Source is designed for optimal use with OP-OPM21 Optical Power Meter for measuring optical loss on both single mode and multimode fiber cable.	

### Order Information

Model	Kit Include
OP-OLS11	OP-OLS11 Optical Light Source, 3pcs 1.5V batteries, AC Adaptor, User Manual and Soft carrying case.

### Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.

## Contact OPTOSTAR

### Shenzhen Optostar Optoelectronics Co., Ltd

Address: A-14, Haide Building, the Intersection of Nanxin Road and Haide Second Road Nanshan District Shenzhen, China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: [info@optostar.com.cn](mailto:info@optostar.com.cn)

Skype: ouyangroya

Web: [www.optostar.com.cn](http://www.optostar.com.cn)