



Framed E1 Fiber Modem

OP-FM-E1



Shenzhen Optostar Optoelectronics Co., Ltd

2013. 05 (Version 2)

Overview

OP-FM-E1 Framed E1 Fiber Modem provides one Framed E1 interface and one optical interface to achieve interface conversion, rate conversion and timeslot extraction from E1 to Optical. When unframed mode, the data channel rate is 2.048Mbps. The device has inter-set loop test function to facilitate the project launching and daily maintenance

Product Features


- Based on self -copyright IC
- Can detect the reason of optical signal losing is that the device power-off or transmission fiber broken, and indicate on LED
- Provide 2 impedances: 75 Ohm unbalance and 120 Ohm balance;
- After strict testing and practical verification system, completely comply with protocol ITU-T V.35, G.703, G.704
- The hardware realizes any one of 31 time slot any time slot optional (valid when framed)
- Have three Loop Back Mode: E1 interface Loop Back (ANA)、 V.35 interface Loop Back(DIG)、 Command the remote V.35 interface Loop Back(REM)
- Have pseudo random code test function, easily line opened, can be used as a 2M BER Tester
- AC 220V, DC-48V, DC+24V, DC Power and Polarity-Free

Technical Parameter

OP-FM-E1 Framed E1 Fiber Modem	
Optical interface	
Multi-mode Fiber	
Diameter of fiber core	50/125um, 62.5/125um
Transmission distance	5Km @ 62.5 / 125um single mode fiber, attenuation (3dbm/km)Wave Length: 820nm
Transmitting power	-12dBm (Min) ~-9dBm (Max)
Receiver sensitivity	-28dBm (Min)
Link budget	16dBm
Connector	SC/FC
Single-mode Fiber	
Diameter of fiber core	8/125um, 9/125um
Transmission distance	40Km @ 9 / 125um single mode fiber, attenuation (0.35dbm/km)
Wave Length	1310nm
Transmitting power	-9dBm (Min) ~-8dBm (Max)
Receiver sensitivity	-27dBm (Min)
Link budget	18dBm
Connector	SC/FC
E1 Interface	
Interface rate	n*64Kbps±50ppm
Interface Standard	comply with protocol G.703
Interface Code	HDB3
E1 Impedance	75 Ω (unbalance), 120 Ω (balance)
Jitter tolerance	In accord with protocol G.742 and G.823
Allowed Attenuation	0~6dBm
Dimension	
Product Size	216X140X31mm(WDXH)
Simple packaging	274X193X84mm(WDXH)
Piece Weight	1.2KG
Operation Environment	
Operating temperature	0°C~50°C

Storing temperature	-40°C~+70°C
Relative humidity	95 %
No causticity and solvent, dust free, and no strong magnetic interference.	
Power	
Voltage	AC180V ~ 260V; DC -48V; DC +24V
Consumption	≤5W
Warranty	2 Year Warranty, Life-time Maintenance

Application



Order Information

Model	Description
OP-FM-E1	Framed E1 Fiber Modem

Package include

No	Package List
1	Framed E1 Fiber Modem
2	User Guide
3	Warranty Card

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.



Contact OPTOSTAR

Shenzhen Optostar Optoelectronics Co., Ltd

Address:A-14,Haide Building,the Intersection of Nanxin Road and Haide Second Road Nanshan District Shenzhen,China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: info@optostar.com.cn

Skype:ouyangroya

Web: www.optostar.com.cn