



Metal Fiber Termination Box

OP-OTB-TM-C



Shenzhen Optostar Optoelectronics Co., Ltd

2011. 06 (Version 2)

Overview

Fiber optic terminal box is available for the distribution and terminal connection for various kinds of optical fiber system, especially suitable for mini-network terminal distribution, in which the optical cables, patch cores or pigtails are connected.

Model: OP-OTB-TM-C is a metal terminal box, 12 ports, for outdoor wall mounted or pole mounted using.

Product Features

- Cold-roll steel, electrostatic painting
- ABS splice tray inside, 12 fibers per tray
- Suitable for different adapters: SC, FC, ST, LC ...
- Max. 12pcs adapters can be loaded
- 4, 6, 8, 12, 24... fibers can be spliced inside
- Outdoor, indoor using, IP65
- 4pcs cable entry ports

Application

- Suitable for Pigtail, ribbon and bunch cable connect distribution
- Used for wall-mounted applications
- Used in FTTH, Telecommunications, CATV ect.

Technical Parameter

Operating temperature: -5~+40℃

Relative humidity: ≤85%(+30℃)

Atmospheric pressure: 70~106Kpa

Durability: >1000 times



Order Information

Model	Description
OP-OTB-TM-C	12 cores 300x250x150 mm Max. 12pcs adapters

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.

Contact OPTOSTAR

Shenzhen Optostar Optoelectronics Co., Ltd

Address:A-14,Haide Building,the Intersection of Nanxin Road and Haide Second Road Nansha n District Shenzhen,China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: info@optostar.com.cn

Skype:ouyangroya

Web: www.optostar.com.cn