



Optical Power Meter

OP-OPM21A/ OP-OPM21C



Shenzhen Optostar Optoelectronics Co., Ltd

2013. 02 (Version 2)

Overview

OP-OPM21 optical power meter is a handheld optical power meter, newly released in 2007, which can be used for absolute optical power measurements as well as for relative loss measurements in optic fiber networks. An $\varnothing 1.0\text{mm}$ photosensitive area photodiode is used to significantly improve the stability and the reliability. It features ingenious appearance, wide range of power measurement, high accuracy, user self-calibration function and reference power level storage.

Product Features

- Wide dynamic measurement range (up to 80dB)
- Reference power level storage(Ref Setting)
- User self-calibration function
- Comfortable LCD display and backlight LCD display supports
- night operation.
- Power measurements in dBm or mw and insertion loss in dB
- 10 minutes Auto-off function can be activated or deactivated.
- AA alkaline batteries can last more than 140 hours, AC adaptor also available
- Low battery indication

APPLICATIONS

- Telecom Maintenance
- CATV Maintenance
- Fiber Optic lab testing
- Other Fiber Optic Measurements

Technical Parameters

MODEL	OP-OPM21A	OP-OPM21C
Wavelength(nm)	800~1700nm	
Detector Type	InGaAs	
Detector Size	Ø 1.0mm	
Measurement Range (dBm)	-70~+10	-50~+30
Uncertainty	±5%	
Calibrated Wavelength(nm)	850,1300,1310,1490,1550,1625	
Resolution(dB)	0.01	
Optical Connector	FC(interchangeable SC,ST) / as well as 2.5mm universal	
Power Supply	Alkaline Battery(3 AA 1.5V batteries); AC Adaptor(9V)	
Battery Operating Time	140 h with 1.5V Battery(3pcs)	
Operating Temperature(°C)	-10 ~ +60	
Storage Temperature(°C)	-25 ~ +70	
Relative Humidity	0 to 95% (non-condensing)	
Dimension(mm)	190X100X50	
Weight(g)	370	

Order Information

Model	Kit Include
All OP-OPM21 Models	OP-OPM21 Optical Power Meter, 3pcs 1.5V batteries, AC Adaptor, User Manual, Cotton swabs and Soft carrying case.

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.

Contact OPTOSTAR

Shenzhen Optostar Optoelectronics Co., Ltd

Address: A-14, Haide Building, the Intersection of Nanxin Road and Haide Second Road Nanshan District Shenzhen, China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: info@optostar.com.cn

Skype: ouyangroya

Web: www.optostar.com.cn