



3 Ports Multimode FWDM (1310/1550nm)



Shenzhen Optostar Optoelectronics Co., Ltd

2013. 05 (Version 2)


Overview

OPTOSTAR Multimode FWDM utilizes thin film coating technology and proprietary design of non-flux metal bonding micro optics packaging. It provides low insertion loss, high channel isolation, low temperature sensitivity and epoxy free optical path.

Product Features

- Wide Operating Wavelength Range
- Low insertion loss
- Ultra Flat Wide Passband
- High Channel Isolation
- High stability and reliability
- Epoxy-free on Optical Path

Package Dimension



Technical Parameter

Parameter		FWDM 5/3	FWDM 3/5
Channel Wavelength (nm)		1500~1600	1260~1360
Reflect Channel Wavelength (nm)		1260~1360	1500~1600
Insertion Loss (dB)	Reflect Channel	≤0.5	
	Pass Channel	≤0.6	
Insertion Loss Variation (dB)		<0.3	
Isolation (dB)	Reflect Channel	>15	
	Pass Channel	>40	
Insertion Loss Temperature Sensitivity(dB/°C)		<0.005	
Polarization Dependent Loss (dB)		<0.1	
Polarization Mode Dispersion (ps)		<0.1	
Directivity (dB)		>50	
Return Loss (dB)		>30	
Maximum Power Handling (mW)		300	
Operating Temperature(°C)		-10~+75	
Storage Temperature(°C)		-40~+85	
Package dimension(mm)		Φ5.5x34 (L38 for 900um Loose tube)	

- 1、Above specifications are for devices without connector.
- 2、Specifications may change without notice.



Application

- System Monitoring
- WDM Network
- Transmitters and Fiber lasers
- Fiber Optical amplifier
- Fiberoptic Instruments

Order Information

Description
3 Ports Multimode FWDM (1310/1550nm)
Note: Fiber Type: 50/125um MM fiber, 62.5/125um MM fiber (optional) Fiber Length: 1m, 2m (optional) In/Out Connector: None, FC/APC, FC/PC, SC/APC, SC/PC, ST, LC/PC, LC/APC, E2000, custom (Optional) Wavelength: 1310 pass/1550 reflect, 1550 pass/1310 reflect (Optional)

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTOSTAR before they become applicable to any particular order or contract. In accordance with the OPTOSTAR policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTOSTAR or others. Further details are available from any OPTOSTAR sales representative.

Contact OPTOSTAR

Shenzhen Optostar Optoelectronics Co., Ltd

Address: A-14, Haide Building, the Intersection of Nanxin Road and Haide Second Road Nanshan District Shenzhen, China .

Tel: +86-755-26400198 +86-755-26400288 Fax: +86-755-26411001

Email: info@optostar.com.cn

Skype: ouyangroya

Web: www.optostar.com.cn